

ORBEA



KERAM 20.

SE TROUVE DANS CES COULEURS:



NOIR-BLANC (SATIN)



JAUNE CLAIR-BLEU CLAIR
(BRILLANT)



BLEU ÉLECTRIQUE-JAUNE
FLUO (SATIN)



GRIS PERLE-MENTE
(BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Keram, compatible 2,8mm tires
FOURCHE	SR Suntour XCR RL-Coil 100mm QR
PLATEAU DE PEDALIER	FSA Bosch-IG3 E-bike 36t
DIRECTION	FSA 1-1/8 - 1-1/2" Integrated
CINTRE	Orbea OC-I Riser 740mm
POTENCE	Orbea OC-II
MANETTES	Shimano Deore M6000
FREINS	Shimano M315 Hydraulic Disc
PIGNON	Sun Race 11-42t 10-Speed
DERAILLEUR ARRIÈRE	Shimano Deore M6000 GS Shadow Plus
CHAINE	KMC X10e
ROUES	Orbea Black Rock 23c Disc
PNEUS	Kenda K1153 2,35" 30TPI
PEDALE	VP-536 Black
TIGE SELLE	Orbea OC-I 31.6x400mm
	Orbea Digit 31.6x400mm
SELLE	Selle Royal 2077 DRN
CADENAS	Axa battery down tube lock
SUPPORT CYCLO	
MOTEUR	BOSCH Active Plus 25 kmh
BATTERIE	BOSCH Performance 500Wh
BIELLE	FSA CK-602 Bosch IG3 170mm

GÉOMÉTRIE

TAILLE	S	M	L
1 - SEAT_TUBE	418	450	530
2 - TOP_TUBE	550	570	605
3 - HEAD_TUBE	130	130	150
4 - CHAIN_STAY		481	
5 - BB_HEIGHT	298	305	305
6 - BB_DROP	52,5	63	63
7 - WHEELBASE	1102	1133	1170
8 - HEAD_ANGLE	69°	68°	68°
9 - SEAT_ANGLE		73°	
10 - STANDOVER	792	822	855
11 - REACH	360	374	403
12 - STACK	616	637	656
13 - FORK_LENGTH	490	508	658

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S-27	170	70	740
M-27	170	70	740
L-27	170	70	740

* La dimension du guidon est centre-centre

