

ORBEA



KERAM COMFORT 20.

SE TROUVE DANS CES COULEURS:



BLEU



ORANGE-NOIR (BRILLANT)



ARGENT-NOIR (SATIN)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Keram, compatible 2,8mm tires
FOURCHE	SR Suntour NEX E-25 63mm Disc
PLATEAU DE PEDALIER	FSA Bosch-IG3 E-bike 36t
DIRECTION	FSA 1-1/8 - 1-1/2" Integrated
CINTRE	Orbea Comfort Riser Alu 660mm
	Orbea OC-I Riser 740mm
POTENCE	Orbea Black Adjustable
	Orbea OC-II 90mm
MANETTES	Shimano Deore M6000
FREINS	Shimano M315 Hydraulic Disc
PIGNON	Shimano HG50 11-36t 10-Speed
DERAILLEUR ARRIÈRE	Shimano Deore M6000 GS Shadow Plus
CHAINE	KMC X10e
ROUES	Orbea Black Rock 23c Disc
PNEUS	Kenda K935 1,65" Reflex
PEDALE	VP-615 Black
TIGE SELLE	Orbea 31.6x350mm w/Suspension
	Orbea OC-I 31.6x400mm
SELLE	Selle Royal Milo Plus HR
	Selle Royal Milo Plus DR
	Selle Royal 2077 DRN
PORTE-BAGAGE ARRIÈRE	PORTABULTOS DE ACERO PARA RUEDAS DE 26 Y 28 NEGRO
GARDE-BOUE	SKS 28" 65mm
ÉCLAIRAGE AVANT	Spanninga Kendo 15 lux
ÉCLAIRAGE ARRIÈRE	Spanninga Lineo
COUVRE-CHAÎNES	FSA Bosch IG3 36-38t
CADENAS	Axa Solid Plus frame lock + battery down tube lock
SUPPORT CYCLO	Yuen I YRA-60B Kickstand
MOTEUR	BOSCH Active Plus 25 kmh
BATTERIE	BOSCH Performance 500Wh
BIELLE	FSA CK-602 Bosch IG3 170mm
BLOCAGE	Safety Lock

GÉOMÉTRIE

TAILLE	S	M	L
1 - SEAT_TUBE	418	450	530
2 - TOP_TUBE	550	570	605
3 - HEAD_TUBE	130	130	150
4 - CHAIN_STAY		481	
5 - BB_HEIGHT	298	305	305
6 - BB_DROP	52,5	63	63
7 - WHEELBASE	1102	1133	1170
8 - HEAD_ANGLE	69°	68°	68°
9 - SEAT_ANGLE		73°	
10 - STANDOVER	792	822	855
11 - REACH	360	374	403
12 - STACK	616	637	656
13 - FORK_LENGTH	490	508	658

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	170	90	660
M	170	90	660
L	170	90	660

* La dimension du guidon est centre-centre

