

ORBEA



WILD HT 20 29 19.

SE TROUVE DANS CES COULEURS:



NOIR (MAT-BRILLANT)



ROUGE-NOIR (BRILLANT-MAT)



BLEU-GRIS (BRILLANT)



MAUVE-NOIR (MAT)

SPÉCIFICATIONS ET OPTIONS

CADRE	ORBEA WILD 2018 Alloy 12X148 for Bosch
FOURCHE	Fox 34 Float Performance 120 3-Position QR15x110 E-Bike Optimized
	Fox 34 Float Factory 120 FIT4 3-Pos-Adj QR15x110 Kashima
PLATEAU DE PEDALIER	FSA Bosch E-bike 14t Boost
BIELLE	Miranda Delta 152mm
DIRECTION	Acros Alloy 1-1/8 - 1-1/2" Integrated
CINTRE	Race Face Ride 35 20mm Rise 760mm
POTENCE	Race Face Ride 35mm interface
MANETTES	SRAM NX Eagle Single click
FREINS	SRAM Guide Hydraulic disc
	Sram Code RSC Hydraulic Disc
PIGNON	SRAM NX PG-1230 Eagle 11-50t 12-Speed
DERAILLEUR ARRIÈRE	SRAM NX Eagle
CHAINE	SRAM NX Eagle 12-Speed
ROUES	DT H-1900 Spline 30c TLR 15/110mm IS (6-bolt)
	DT H-1700 Spline 30c TLR 15/110mm IS (6-bolt)
PNEUS	Kenda 1211E Nevegal 2 29x2.4" 60TPI TLR (E-MTB specific)
PEDALE	VP-537 Black
TIGE SELLE	Race Face Aeffect Dropper 31.6x385/125mm
	Crank brothers Highline 31,6x425/150mm
SELLE	Selle Royal 2077 DRN
CADENAS	Abus battery power tube lock PLUS
MOTEUR	BOSCH Performance CX 25 kmh
BATTERIE	BOSCH Performance 500Wh
ÉCRAN	BOSCH Performance Purion
CHARGEUR	Compact Charger 2A (100-240V) Worldwide
	Fast Charger 6A (220-240V)

GÉOMÉTRIE

TAILLE	S	M	L	XL
1 - SEAT_TUBE	390	390	415	440
2 - TOP_TUBE	575	595	624	653
3 - HEAD_TUBE	115	130	145	160
4 - CHAIN_STAY	470			
5 - BB_DROP	63			
6 - WHEELBASE	1139	1160	1190	1221
7 - HEAD_ANGLE	67º			
8 - SEAT_ANGLE	72.5º			
9 - STANDOVER	798	805	816	826
10 - REACH	375	390	415	440
11 - STACK	364	647	661	675
12 - FORK_LENGTH	527			
13 - OFFSET	51			

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	152	50	760
M	152	50	760
L	152	50	760
XL	152	50	760

* La dimension du guidon est centre-centre

