

ORBEA



WILD HT 20 29S 19.

SE TROUVE DANS CES COULEURS:



BRILLIANT ROUGE-NOIR
(BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	ORBEA Wild 2019 Alloy 12X148 Hydroformed Alloy 140mm Travel Boost 12X148 for Shimano E8000/7000
FOURCHE	Fox 34 Float Performance 120 3-Position QR15x110 E-Bike Optimized Fox 34 Float Factory 120 FIT4 3-Pos-Adj QR15x110 Kashima
PLATEAU DE PEDALIER	SRAM X-SYNC Eagle 34T
BIELLE	Miranda Delta 152mm
DIRECTION	Acros Alloy 1-1/8 - 1-1/2" Integrated
CINTRE	Race Face Ride 35 20mm Rise 760mm
POTENCE	Race Face Ride 35mm interface
MANETTES	SRAM NX Eagle Single click
FREINS	SRAM Guide Hydraulic disc Sram Code RSC Hydraulic Disc
PIGNON	SRAM NX PG-1230 Eagle 11-50t 12-Speed
DERAILLEUR ARRIÈRE	SRAM NX Eagle
CHAÎNE	SRAM NX Eagle 12-Speed
ROUES	DT H-1900 Spline 30c TLR 15/110mm IS (6-bolt) DT H-1700 Spline 30c TLR 15/110mm IS (6-bolt)
PNEUS	Kenda 1211E Nevegal 2 29x2.4" 60TPI TLR (E-MTB specific)
PEDALE	VP-537 Black
TIGE SELLE	Race Face Aeffect Dropper 31.6x385/125mm Crank brothers Highline 31,6x425/150mm
SELLE	Selle Royal 2077 DRN
CADENAS	Abus battery down tube lock
GUIDE-CHAÎNE	Orbea OC chainguide
MOTEUR	Shimano Steps DU-E8000 25kmh
BATTERIE	Shimano Steps E8010
ÉCRAN	Shimano Steps SC-E8000
CHARGEUR	Shimano Steps E6002 Shimano Steps E6000
REMOTE1	Shimano E8000 switch unit for assist

GÉOMÉTRIE

TAILLE	S	M	L	XL
1 - SEAT_TUBE	390	390	415	440
2 - TOP_TUBE	575	595	624	653
3 - HEAD_TUBE	115	130	145	160
4 - CHAIN_STAY			445	
5 - BB_DROP			63	
6 - WHEELBASE	1113	1134	1165	1195
7 - HEAD_ANGLE			67°	
8 - SEAT_ANGLE			72.5°	
9 - STANDOVER	798	805	816	826
10 - REACH	375	390	415	440
11 - STACK	364	647	661	675
12 - FORK_LENGTH			527	
13 - OFFSET			51	

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	152	50	760
M	152	50	760
L	152	50	760
XL	152	50	760

* La dimension du guidon est centre-centre

