

**ORBEA**



## KERAM 15 19.

SE TROUVE DANS CES COULEURS:



NOIR (MAT-BRILLANT)



ARGENT-ROUGE (MAT)



ROUGE (BRILLANT-MAT)



BLEU MÉTAL (BRILLANT-MAT)

## SPÉCIFICATIONS ET OPTIONS

|                            |  |
|----------------------------|--|
| <b>CADRE</b>               | Orbea Keram 2019, Hydroformed Alloy 6061, Hide out battery technology, bottle cage and dual battery compatible and hidden kickstand compatible |
| <b>FOURCHE</b>             | RockShox 30 Silver TK 100 Air Remote QR  |
| <b>PLATEAU DE PEDALIER</b> | Prowheel EB04 36t  |
|                            | Prowheel EB04 38t w/chainguard   |
| <b>DIRECTION</b>           | Acros Alloy 1-1/8 - 1-1/2" Integrated  |
| <b>CINTRE</b>              | Orbea OC-I Riser 740mm   |
| <b>POTENCE</b>             | Orbea OC-II  |
| <b>MANETTES</b>            | Shimano Deore M6000  |
| <b>FREINS</b>              | Shimano MT200 Hydraulic Disc   |
| <b>PIGNON</b>              | Sun Race 11-42t 10-Speed   |
| <b>DERAILLEUR ARRIÈRE</b>  | Shimano Deore M6000 GS Shadow Plus Direct Mount  |
| <b>CHAINE</b>              | KMC e10 Turbo Silver   |
| <b>ROUES</b>               | Orbea Tryp 25c Disc Tubeless ready   |
| <b>PNEUS</b>               | Kenda K1153 2.35" 30TPI  |
| <b>PEDALE</b>              | VP-537 Black   |
| <b>TIGE SELLE</b>          | Orbea OC-I 31.6x400mm  |
| <b>SELLE</b>               | Selle Royal 2077 DRN   |
| <b>CADENAS</b>             | Abus battery down tube lock  |
| <b>SUPPORT CYCLO</b>       | Ursus Mooi 40mm rear adjustable  |
| <b>MOTEUR</b>              | BOSCH Active Plus 25 kmh   |
| <b>BATTERIE</b>            | BOSCH Performance 500Wh  |
|                            | Dual Battery conection (no battery)  |
| <b>ÉCRAN</b>               | BOSCH Performance Purion   |
| <b>CHARGEUR</b>            | Compact Charger 2A (100-240V) Worldwide  |
|                            | Fast Charger 6A (220-240V)   |

## GÉOMÉTRIE

| TAILLE                  | S-27.5" | M-29" | L-29 | XL-29" |
|-------------------------|---------|-------|------|--------|
| <b>1 - SEAT_TUBE</b>    | 400     | 405   | 457  | 515    |
| <b>2 - TOP_TUBE</b>     | 538     | 569   | 603  | 638    |
| <b>3 - HEAD_TUBE</b>    | 105     | 114   | 133  | 144    |
| <b>4 - CHAIN_STAY</b>   |         | 475   |      |        |
| <b>5 - BB_HEIGHT</b>    | 307     | 313   | 313  | 313    |
| <b>6 - BB_DROP</b>      | 43      | 63    | 63   | 63     |
| <b>7 - WHEELBASE</b>    | 1112    | 1149  | 1173 | 1210   |
| <b>8 - HEAD_ANGLE</b>   | 67      | 67    | 68   | 68     |
| <b>9 - SEAT_ANGLE</b>   |         | 73°   |      |        |
| <b>10 - STANDOVER</b>   | 798     | 825   | 861  | 893    |
| <b>11 - REACH</b>       | 355     | 375   | 402  | 430    |
| <b>12 - STACK</b>       | 600     | 636   | 659  | 752    |
| <b>13 - FORK_LENGTH</b> | 518     | 530   | 530  | 530    |
| <b>14 - OFFSET</b>      | 42mm    | 51mm  | 51mm | 51mm   |

## ERGONOMIE

| TAILLE       | BIELLE | POTENCE | CINTRE |
|--------------|--------|---------|--------|
| <b>S-27</b>  | 170    | 70      | 740    |
| <b>M-29</b>  | 170    | 70      | 740    |
| <b>L-29</b>  | 170    | 70      | 740    |
| <b>XL-29</b> | 170    | 70      | 740    |

\* La dimension du guidon est centre-centre

