

ORBEA



KERAM MAX 19.

SE TROUVE DANS CES COULEURS:



NOIR (MAT-BRILLANT)



ARGENT-ROUGE (MAT)



ROUGE (BRILLANT-MAT)



BLEU MÉTAL (BRILLANT-MAT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Keram 2019, Hydroformed Alloy 6061, Hide out battery technology, bottle cage and dual battery compatible and hidden kickstand compatible
FOURCHE	RockShox Recon RL 120 Air Remote Q15x110 e-MTB
PLATEAU DE PEDALIER	Prowheel EB04 36t
	Prowheel EB04 38t w/chainguard
DIRECTION	Acros Alloy 1-1/8 - 1-1/2" Integrated
CINTRE	Orbea OC-I Riser 740mm
POTENCE	Orbea OC-II
MANETTES	Shimano XT M8000
FREINS	Shimano MT400 Hydraulic Disc
PIGNON	Sun Race 11-46t 11-Speed
DERAILLEUR ARRIÈRE	Shimano XT M8000 GS Shadow Plus Direct Mount
CHAINE	KMC e11 Turbo Silver
ROUES	Mach1 Klix 23c Tubeless Ready
PNEUS	Maxxis Ikon 2.20" FB 60 TPI Dual
PEDALE	VP-537 Black
TIGE SELLE	Orbea OC-I 31.6x400mm
SELLE	Selle Royal 2077 DRN
CADENAS	Abus battery down tube lock
SUPPORT CYCLO	
	Ursus Mooi 40mm rear adjustable
MOTEUR	BOSCH Active Plus 25 kmh
BATTERIE	BOSCH Performance 500Wh
	Dual Battery conection (no battery)
ÉCRAN	BOSCH Performance Purion
CHARGEUR	Compact Charger 2A (100-240V) Worldwide
	Fast Charger 6A (220-240V)

GÉOMÉTRIE

TAILLE	S-27.5"	M-29"	L-29	XL-29"
1 - SEAT_TUBE	400	405	457	515
2 - TOP_TUBE	538	569	603	638
3 - HEAD_TUBE	105	114	133	144
4 - CHAIN_STAY	475			
5 - BB_HEIGHT	307	313	313	313
6 - BB_DROP	43	63	63	63
7 - WHEELBASE	1112	1149	1173	1210
8 - HEAD_ANGLE	67	67	68	68
9 - SEAT_ANGLE	73º			
10 - STANDOVER	798	825	861	893
11 - REACH	355	375	402	430
12 - STACK	600	636	659	752
13 - FORK_LENGTH	518	530	530	530
14 - OFFSET	42mm	51mm	51mm	51mm

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S-27	170	70	740
M-29	170	70	740
L-29	170	70	740
XL-29	170	70	740

* La dimension du guidon est centre-centre

