

**ORBEA**



## GAIN D20 19.

SE TROUVE DANS CES COULEURS:



ORANGE-NOIR (BRILLANT)



GRIS PERLE-BLANC  
(MAT-BRILLANT)



GRAPHITE-ANTHRACITE (MAT)

## SPÉCIFICATIONS ET OPTIONS

<b>CADRE</b>	Orbea Gain Hydro, Aluminum 6000 series, Orbea Tube Shaping, Flat Mount Disc Brakes, 135x9 QR, Carrier and Mudguards compatible, max 700x40C, Inner Cable routing, Ebikemotion X35 specific, integrated battery, in
<b>FOURCHE</b>	Speed 400mm Carbon Flat mount
<b>PLATEAU DE PEDALIER</b>	Shimano Ultegra R8000 34x50t
<b>DIRECTION</b>	1-1/8" Semi-Integrated
<b>CINTRE</b>	FSA Energy Compact
	FSA K-Force Compact
<b>POTENCE</b>	FSA Energy
	FSA OS-99 CSI
<b>MANETTES</b>	Shimano ST-8020
<b>FREINS</b>	Shimano R8070 Hydraulic Disc
<b>PIGNON</b>	Shimano Ultegra R8000 11-32t 11-Speed
<b>DERAILLEUR ARRIÈRE</b>	Shimano Ultegra R8000 GS
<b>DERAILLEUR AVANT</b>	Shimano Ultegra R8000
<b>CHAÎNE</b>	KMC e11 Turbo Silver
<b>ROUES</b>	Ready GR
	Mavic Cosmic Pro Carbon Disc UST
<b>PNEUS</b>	Hutchinson Fusion 5 All Season TLR 700x28
	Hutchinson Fusion 5 All Season TLR 700x25
<b>PÉDALE</b>	N/A
<b>TIGE SELLE</b>	FSA SL-K SB20 27.2x350mm Di2 compatible
	FSA K-Force SB25 27.2x350mm Di2 compatible
<b>SELLE</b>	Prologo Kappa Space STN size 147mm
<b>MOTEUR</b>	Ebikemotion X35 25kmh
<b>BATTERIE</b>	Ebikemotion 36V/6.9Ah
<b>RUBAN DE GUIDON</b>	Velo Anti-Slippery/Shock Proof
<b>CHARGEUR</b>	Ebikemotion X35
<b>REMOTE1</b>	Ebikemotion iWoc ONE

## GÉOMÉTRIE

TAILLE	XS	S	M	L	XL
<b>1 - SEAT_TUBE</b>	460	510	555	585	610
<b>2 - TOP_TUBE</b>	522	546	560	574	595
<b>3 - HEAD_TUBE</b>	109	127	150	176	203
<b>4 - CHAIN_STAY</b>			430		
<b>5 - BB_HEIGHT</b>	281	281	283	283	285
<b>6 - BB_DROP</b>	70	70	68	68	66
<b>7 - WHEELBASE</b>	1016	1022	1037	1051	1067
<b>8 - HEAD_ANGLE</b>	71°	72°	72°	72°	72.3°
<b>9 - SEAT_ANGLE</b>	75°	74°	74°	74°	73.5°
<b>10 - STANDOVER</b>	754	782	815	829	876
<b>11 - REACH</b>	378	387	395	402	410
<b>12 - STACK</b>	535	555	575	600	625
<b>13 - FORK_LENGTH</b>			400		
<b>14 - OFFSET</b>			51		

## ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
<b>47</b>	170	90	400
<b>49</b>	170	100	400
<b>51</b>	170	100	420
<b>53</b>	172.5	110	420
<b>55</b>	172.5	110	420
<b>57</b>	172.5	110	440
<b>60</b>	175	120	440

\* La dimension du guidon est centre-centre

