

ORBEA



GAIN F30 19.


SE TROUVE DANS CES COULEURS:



NOIR (MAT-BRILLANT)



VERT (MAT-BRILLANT)



BLEU (MAT-BRILLANT)



BRILLANT ROUGE-NOIR
(MAT-BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Gain Hydro, Aluminum 6000 series, Orbea Tube Shaping, Flat Mount Disc Brakes, 135x9 QR, Carrier and Mudguards compatible, max 700x40C, Inner Cable routing, Ebikemotion X35 specific, integrated battery, in
FOURCHE	Speed 400mm Carbon Flat mount
PLATEAU DE PEDALIER	Shimano Claris R2000 34x50t
DIRECTION	1-1/8" Semi-Integrated
CINTRE	Orbea OC-I Riser 640mm
POTENCE	Orbea OC-II
MANETTES	Shimano Claris SL-R2000
FREINS	Shimano MT200 Hydraulic Disc
PIGNON	Shimano HG50 11-34t 8-Speed
DERAILLEUR ARRIÈRE	Shimano Claris RD-R2000-GS
DERAILLEUR AVANT	Shimano Claris FD-R2000-F
CHAINE	KMC X8
ROUES	Airline Corsa
PNEUS	Kenda K1067 700x38C Reflective type+puncture protection
PEDALE	VP-537 Black
TIGE SELLE	Orbea OC-I 27.2x350mm
SELLE	Selle Royal Scientia A2
PORTE-BAGAGE ARRIÈRE	Tubus Fly
GARDE-BOUE	Orbea SKS 46S 700x45C + Spanninga Kendo(F)/Pixeo(R) Lights Orbea SKS 46S 700x45C Black
ÉCLAIRAGE AVANT	
ÉCLAIRAGE ARRIÈRE	
SUPPORT CYCLO	Ursus Mooi 40mm rear adjustable
MOTEUR	Ebikemotion X35 25kmh
BATTERIE	Ebikemotion 36V/6.9A
CHARGEUR	Ebikemotion X35
REMOTE1	Ebikemotion iWoc ONE
REMOTE2	Ebikemotion iWoc TRIO

GÉOMÉTRIE

TAILLE	XS	S	M	L	XL
1 - SEAT_TUBE	460	510	555	585	610
2 - TOP_TUBE	522	546	560	574	595
3 - HEAD_TUBE	109	127	150	176	203
4 - CHAIN_STAY			430		
5 - BB_HEIGHT	281	281	283	283	285
6 - BB_DROP	70	70	68	68	66
7 - WHEELBASE	1016	1022	1037	1051	1067
8 - HEAD_ANGLE	71°	72°	72°	72°	72.3°
9 - SEAT_ANGLE	75°	74°	74°	74°	73.5°
10 - STANDOVER	754	782	815	829	876
11 - REACH	378	387	395	402	410
12 - STACK	535	555	575	600	625
13 - FORK_LENGTH			400		
14 - OFFSET			51		

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
46	170	70	640
51	170	70	640
56	170	70	640
59	170	70	640
61	170	70	640

* La dimension du guidon est centre-centre

