

ORBEA



ORCA M20i 19.

SE TROUVE DANS CES COULEURS:



VERT-BLEU (MAT)



GRAPHITE-NOIR (MAT)



ROUGE-NOIR (MAT-BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Orca carbon OME, monocoque,tapered 1-1/8" - 1,5", PF 86mm, powermeter compatible, brake internal cable routing, EC/DC compatible, 130mm rear spacing, 27,2mm seat tube.
FOURCHE	Orca OME carbon fork, full carbon steerer, tapered 1-1/8" - 1,5", carbon dropouts
PLATEAU DE PEDALIER	Shimano Ultegra R8000 34x50t
	FSA Gossamer Pro 32x48t
	Shimano Ultegra R8000 39x53t
DIRECTION	FSA 1-1/8 - 1-1/2" Integrated Aluminium Cup ACB Bearings
CINTRE	FSA Gossamer Compact
POTENCE	Orbea OC-II
MANETTES	Shimano Ultegra R8050 Di2
FREINS	Shimano Ultegra R8000
PIGNON	Shimano 105 R7000 11-28t 11-Speed
	Shimano 105 R7000 11-30t 11-Speed
	Shimano 105 R7000 11-32 11-Speed (RD GS)
DERAILLEUR ARRIÈRE	Shimano Ultegra Di2 R8050 GS
DERAILLEUR AVANT	Shimano Ultegra Di2 R8050
CHAINE	Fsa Team Issue
ROUES	Mavic Aksium
PNEUS	Vittoria Rubino Foldable 700x25 60TPI G+
PEDALE	N/A
TIGE SELLE	Orbea OC-II Carbon 27.2x350mm
SELLE	Selle Royal Seta RS
RUBAN DE GUIDON	Velo Eva
FREIN ARRIÈRE	Shimano Ultegra R8000
--	

GÉOMÉTRIE

TAILLE	47	49	51	53	55	57	60
1 - SEAT_TUBE	440	460	480	500	520	540	570
2 - TOP_TUBE	507	522	535	550	561	575	591
3 - HEAD_TUBE	110	125	140	155	175	195	220
4 - CHAIN_STAY	408						
5 - BB_HEIGHT	269.5						
6 - BB_DROP	72	72	72	70	70	70	70
7 - WHEELBASE	972	977	983	983	991	1001	1015
8 - HEAD_ANGLE	71	71.5	72	72.8	73	73.2	73.2
9 - SEAT_ANGLE	74.5	74	73.7	73.5	73.5	73.2	73.2
10 - STANDOVER	738.5	755.59	773.35	793.2	812.79	831.48	857.84
11 - REACH	367	370	375	382	387	393	402
12 - STACK	515	530	547	564	584	603	627
13 - FORK_LENGTH	375						
14 - OFFSET	50mm	50mm	50mm	43mm	43mm	43mm	43mm

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
47	170	90	400
49	170	100	400
51	170	100	420
53	170	110	420
55	172	110	420
57	172	110	440
60	175	120	440

* La dimension du guidon est centre-centre

