



ALMA H2O.

SE TROUVE DANS CES COULEURS:



NOIR (MAT)- ICE GREEN (BRILLANT)



BLEU INDIGO (MAT)- BRIGHT RED (BRILLANT)



WHITE GRIS- ROUGE MÉT. (BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Alma Hydro Alloy, Boost 12x148, BSA BB, Internal cable routing.
FOURCHE	RockShox Judy Silver TK Remote Solo Air 100 QR15x110 Boost
	RockShox SID Select RL remote Q15X110 Boost DebonAir 100mm
PLATEAU DE PEDALIER	Shimano MT511 32t
DIRECTION	FSA 1-1/8 - 1-1/2" Integrated
CINTRE	OC1 Flat 31.8mm 740mm
POTENCE	OC1 31.8mm interface -7°
MANETTES	Shimano Deore M6100
FREINS	Shimano MT201 Hydraulic Disc
	Shimano M6100 Hydraulic Disc
PIGNON	Shimano SLX M7100 10-51t 12-Speed
DERAILLEUR ARRIÈRE	Shimano SLX M7100 SGS Shadow Plus
CHAINE	Shimano M6100
ROUES	Orbea OC1 25c Tubeless Ready
PNEUS	Maxxis Ikon 2.20" FB 60 TPI Dual
	Maxxis Ikon 2.20" FB 120 TPI 3C Exo TR
PEDALE	N/A
TIGE SELLE	OC2 forge head 27.2 Offset 0
	OC2 Dropper 27.2mm 80mm travel
SELLE	Selle Royal Seta Sport
	Women Kit: OC Grips OD29mm&Selle Italia SLR Boost SuperFlow
	Fizik Taiga S-alloy rail

GÉOMÉTRIE

TAILLE	S	M	L	XL
1 - SEAT_TUBE	400	445	483	533
2 - TOP_TUBE	562	596	620	650
3 - HEAD_TUBE	100	110	120	135
4 - CHAIN_STAY			435	
5 - BB_HEIGHT			309	
6 - BB_DROP			61	
7 - WHEELBASE	1092	1127	1152	1184
8 - HEAD_ANGLE			68°	
9 - SEAT_ANGLE			74,5	
10 - STANDOVER	721	735	791	829
11 - REACH	395	426	448	474
12 - STACK	602	612	621	635
13 - FORK_LENGTH			501,6	
14 - OFFSET			44	

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	170	70	740
M	175	70	740
L	175	90	740
XL	175	100	740

* La dimension du guidon est centre-centre