



## AVANT H40-D.

SE TROUVE DANS CES COULEURS:



BLANC-GRIS (BRILLANT)



SPEED SILVER (MAT)




VERT MILITAIRE-DORÉ (BRILLANT)

## SPÉCIFICATIONS ET OPTIONS

<b>CADRE</b>	Orbea Avant Hydro disc, hydroformed triple butted aluminium, HS 1,5" ICR, BB 68mm - BSC English, Thru Axle 12x142mm rear, thread M12x2 P1, Internal Cable Routing, SP 27,2mm, MMS system.
<b>FOURCHE</b>	Orbea carbon fork 2021, aluminum steerer, 1-1/8" head tube
<b>PLATEAU DE PEDALIER</b>	FSA Omega Megaexo 34x50t
<b>DIRECTION</b>	Acros Alloy 1-1/2" Internal Cable Routing
<b>CINTRE</b>	OC1 Road, reach 80mm, drop 125mm OC1 Road, riser 15mm, reach 70mm, drop 125mm
<b>POTENCE</b>	OC1 31.8mm interface -6°
<b>MANETTES</b>	Shimano Tiagra ST-4700
<b>FREINS</b>	Tektro MD-C550 Mechanical Disc Shimano Tiagra 4770 Hydraulic Disc
<b>PIGNON</b>	Sun Race CSMS1 11-34t 10-Speed
<b>DERAILLEUR ARRIÈRE</b>	Shimano Tiagra 4700 GS
<b>DERAILLEUR AVANT</b>	Shimano Tiagra 4700
<b>CHAÎNE</b>	KMC X10
<b>ROUES</b>	Orbea wheel: Cosra with 12mm E-Thru hubset Shimano RS470 28H
<b>PNEUS</b>	Vittoria Zafiro V Rigid bead 700x28c
<b>TIGE SELLE</b>	Alloy 27.2 Offset 20
<b>SELLE</b>	Selle Royal Seta RS Prologo Akero AGX STN size 155mm
<b>GUIDOLINE</b>	Orbea Eva
<b>BLOCAGE AVANT</b>	Orbea Thru Axle 12x100mm M12x2 P1 Solid
<b>BLOCAGE ARRIÈRE</b>	Orbea Thru Axle 12x142mm M12x2 P1 Solid

## GÉOMÉTRIE

TAILLE	47	49	51	53	55	57	60
<b>1 - SEAT_TUBE</b>	420	445	470	495	520	545	575
<b>2 - TOP_TUBE</b>	511	526	539	553	569	586	597
<b>3 - HEAD_TUBE</b>	122	141	161	180	201	221	241
<b>4 - CHAIN_STAY</b>	425						
<b>5 - BB_HEIGHT</b>	276	276	276	278	278	278	278
<b>6 - BB_DROP</b>	75	75	75	73	73	73	73
<b>7 - WHEELBASE</b>	989	996	1004	1006	1020	1029	1038
<b>8 - HEAD_ANGLE</b>	71°	71.5°	71.9°	72.4°	72.6°	72.8°	73°
<b>9 - SEAT_ANGLE</b>	74.5°	74°	73.75°	73.5°	73.5°	73°	73°
<b>10 - STANDOVER</b>	415	444	470	502	520	550	568
<b>11 - REACH</b>	365	370	375	380	390	395	400
<b>12 - STACK</b>	525	545	565	585	605	625	645
<b>13 - FORK_LENGTH</b>	370						
<b>14 - OFFSET</b>	48	48	48	43	43	43	43



## ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
47	170	90	380
49	170	100	400
51	170	100	420
53	170	100	420
55	172	110	420
57	172	110	440
60	175	120	440

\* La dimension du guidon est centre-centre