



VIBE MID HIO MUD.

SE TROUVE DANS CES COULEURS:



NOIR NUIT (BRILLANT)



BLEU (BRILLANT)



ROUGE FONCÉ MÉTALLISÉ (BRILLANT)



VERT URBAIN (BRILLANT)



VERT CLAIR (BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Vibe Mid Bar Hydro 6061 Hydroform Aluminum 2021, ICR cable routing, Forged BB, 135x9 QR, Flat Mount disc, 700x40 maximum tyre, 1" 1/2 semi head set, 41x86,5 Pressfit BB, carrier and fenders compatible
FOURCHE	Orbea Vibe carbon fork, full carbon, 1-1/5, 700x40 maximum tyre, flat mount disc mount, Thru Axle 12x100mm, Long mudguards compatible.
PLATEAU DE PEDALIER	OC 42t, w/Chainguard
DIRECTION	Acros Alloy 1-1/2" Internal Cable Routing
CINTRE	Alloy 31.8mm 12mm Rise 700mm
POTENCE	OC1 31.8mm interface -6°
MANETTES	Shimano Deore M6100
FREINS	Magura MT5 E-STOP Hydraulic Disc Easy Route Connection
PIGNON	Sun Race CSMZ80 11-51t 12-Speed Metallic E-bike
DERAILLEUR ARRIÈRE	Shimano XT M8100 SGS Shadow Plus
CHAINE	KMC X12
ROUES	Ready GR
PNEUS	Kenda K1052 700x45C Reflective type TLR
TIGE SELLE	Alloy 27.2 Offset 20
SELLE	Brooks Cambium C19 275x184
GARDE-BOUE	CURANA Apollo 55mm
FRONT POSITION LIGHT	Front position light, on head tube, COB Led, On/Off, 60 Lumen, ECE50.
ÉCLAIRAGE AVANT	Lezyne Ebike POWER STVZO PRO E115 inverted position with remote 310 lumens
ÉCLAIRAGE ARRIÈRE	Lezyne FENDER STVZO
BÉQUILLE	Ursus Mooi R90 rear alloy adjustable
MOTEUR	Ebikemotion X35 Plus 25kmh
BATTERIE	Ebikemotion 36V/6.9A 248Wh ANT+
POIGNÉES	Brooks Comfort Cambium 130mm
ÉCRAN	OC monochrome ANT+ LEV
CHARGEUR	Ebikemotion X35
REMOTE2	Ebikemotion iWoc TRIO
BLOCAGE AVANT	Orbea Thru Axle 12x100mm M12x2 P1 Hollow
VIBE TÔLE MYO LITE	
SONNETTE	Knog Oi Classic

GÉOMÉTRIE

TAILLE	S	M	L
1 - SEAT_TUBE	455	490	525
2 - TOP_TUBE		589	
3 - HEAD_TUBE	109	141	160
4 - CHAIN_STAY		435	
5 - BB_HEIGHT		280	
6 - BB_DROP		76	
7 - WHEELBASE	1008	1028	1040
8 - HEAD_ANGLE	71°	71°	71.5°
9 - SEAT_ANGLE	75°	74.5°	74°
10 - STANDOVER	775	806	832
11 - REACH	370	380	390
12 - STACK	550	580	600
13 - FORK_LENGTH		410	
14 - OFFSET		44	
15 - WHEEL_SIZE		712	

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	170	90	700
M	170	90	700
L	170	90	700

* La dimension du guidon est centre-centre