



# VIBE MID H30.

SE TROUVE DANS CES COULEURS:



NOIR NUIT (BRILLIANT)



BLEU (BRILLIANT)



ROUGE FONCÉ MÉTALLISÉ (BRILLIANT)



VERT URBAIN (BRILLIANT)

## SPÉCIFICATIONS ET OPTIONS

<b>CADRE</b>	Orbea Vibe Mid Bar Hydro 6061 Hydroform Aluminum 2021, ICR cable routing, Forged BB, 135x9 QR, Flat Mount disc, 700x40 maximum tyre, 1" 1/2 semi head set, 41x86,5 Pressfit BB, carrier and fenders compatible
<b>FOURCHE</b>	Orbea Vibe carbon fork, full carbon, 1-1/5, 700x40 maximum tyre, flat mount disc mount, Thru Axle 12x100mm, Long mudguards compatible.
<b>PLATEAU DE PEDALIER</b>	OC 42t, w/Chainguard
<b>DIRECTION</b>	Acros Alloy 1-1/2" Internal Cable Routing
<b>CINTRE</b>	Alloy 31.8mm 12mm Rise 700mm
<b>POTENCE</b>	OC1 31.8mm interface -6°
<b>MANETTES</b>	Shimano Deore M4100
<b>FREINS</b>	Magura MT30 Hydraulic Disc Easy Route Connection
<b>PIGNON</b>	Shimano CS-M4100 11-46t 10-Speed
<b>DERAILLEUR ARRIÈRE</b>	Shimano Deore M5120 SGS Shadow Plus
<b>CHAINE</b>	KMC X10
<b>ROUES</b>	Ready GR
<b>PNEUS</b>	Kenda K1052 700x45C Reflective type+puncture protection
<b>TIGE SELLE</b>	OC 27.2 Offset 0, for integrated light
<b>SELLE</b>	Selle Royal Lift 1404 HRN 266x170mm
<b>FRONT POSITION LIGHT</b>	Front position light, on head tube, COB Led, On/Off, 60 Lumen, ECE50.
<b>ÉCLAIRAGE AVANT</b>	Lezyne Ebike POWER STVZO PRO E115 inverted w/rem 310 lumens
<b>ÉCLAIRAGE ARRIÈRE</b>	Lezyne FENDER STVZO seatpost mounting 11 lumens
<b>BÉQUILLE</b>	Ursus Mooi rear adjustable
<b>MOTEUR</b>	Ebikemotion X35 Plus 25kmh
<b>BATTERIE</b>	Ebikemotion 36V/6.9A 248Wh ANT+
<b>ÉCRAN</b>	OC monochrome ANT+ LEV
<b>CHARGEUR</b>	Ebikemotion X35
<b>REMOTE2</b>	Ebikemotion iWoc TRIO
<b>BLOCAGE AVANT</b>	Orbea Thru Axle 12x100mm M12x2 P1 Hollow
<b>VIBE TÔLE MYO LITE</b>	
<b>SONNETTE</b>	Knog Oi Classic

## GÉOMÉTRIE

TAILLE	S	M	L
<b>1 - SEAT_TUBE</b>	455	490	525
<b>2 - TOP_TUBE</b>		589	
<b>3 - HEAD_TUBE</b>	109	141	160
<b>4 - CHAIN_STAY</b>		435	
<b>5 - BB_HEIGHT</b>		280	
<b>6 - BB_DROP</b>		76	
<b>7 - WHEELBASE</b>	1008	1028	1040
<b>8 - HEAD_ANGLE</b>	71°	71°	71.5°
<b>9 - SEAT_ANGLE</b>	75°	74.5°	74°
<b>10 - STANDOVER</b>	775	806	832
<b>11 - REACH</b>	370	380	390
<b>12 - STACK</b>	550	580	600
<b>13 - FORK_LENGTH</b>		410	
<b>14 - OFFSET</b>		44	
<b>15 - WHEEL_SIZE</b>		712	

## ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	170	90	700
M	170	90	700
L	170	90	700

\* La dimension du guidon est centre-centre